

ALPHA

7 YR INDUSTRY
LEADING
LIMITED WARRANTY

» HIGHLIGHTS

- + Simplest maintenance in the industry
- + Toughest frame, front forks and deck in the industry
- + SmoothTrak steering with automatic park brake system
- + Kawasaki Premium FR Engine
- + Proven Hydro-Gear ZT 2100 transmissions for smooth operation and extended life
- + Welded steel deck
- + 11" Castor tyres and 18" drive tyres
- + 11.4 litre fuel capacity
- + Always-on LED lights
- + Reinforced engine guard



TOP SPEED

10.5
KPH

bigdogmowerco.co.nz

Visit your BigDog dealer for details.
Specifications subject to change without notice.

» SPECIFICATIONS

DECKS

CUTTING WIDTH	42" 52"
CUTTING HEIGHT	1.5" to 4.5"
DECK LIFT	Foot Operated
DEPTH	4"
BLADES	42" Deck: 2 52" Deck: 3
BLADE LENGTH	42" Deck: 20.50" 52" Deck: 17.86"
SPINDLES	Aluminium with 3/4" steel shafts and sealed ball bearings with triple protection seals
DRIVE	Electric PTO clutch
CONSTRUCTION	11 ga. fabricated
SPINDLE MOUNTS	Reinforced 14 ga.
IMPACT/TRIM AREAS	1/4" steel bar

DIMENSIONS

DECK SIZE	42"	52"
HEIGHT	39" / 99cm	39" / 99cm
LENGTH	73" / 185.4cm	73" / 185.4cm
OVERALL WIDTH <small>(with discharge chute up)</small>	44.4" / 112.8cm	53.4" / 135.6cm
WEIGHT	227kg	236kg

GENERAL

SEAT	Bolstered high back seat with arm rests and suspension springs
FUEL CAPACITY	11.4 Litre
CUP HOLDER	Yes
FRONT TIRE	11" x 4" – 5, smooth tread
DRIVE TIRE	42" Deck: 18" x 8.50" – 8, turf tread 52" Deck: 18" x 8.50" – 8, turf tread

ENGINE

MANUFACTURER	Kawasaki
HORSEPOWER	42" Deck: Kawasaki FR651V – 21.5 HP 52" Deck: Kawasaki FR691V – 23 HP
COOLING	Air Cooled
ENGINE WARRANTY	3 yrs.

DRIVE SYSTEM

TYPE	Dual Hydrostatic
TRANSMISSION	Hydro-Gear ZT 2100
SPEED	Forward: 0-6.5mph / 10.5kph, Reverse: 0-4mph / 6.4kph
PARKING BRAKES	Patented Automatic

CONSTRUCTION

FRAME	3.25" x 1.5" x 0.120" steel
FRONT AXLE	Fabricated with steel ball bearings
FRONT CASTER WHEELS	Steel roller bearings
FRONT CASTER FORKS	Fabricated 1/4" steel

ALPHA